

MAF300LD / M series


AIR UNIT (MIST / MICROMIST FILTER)




mindman



Symbol



D: 0.3µm



M: 0.01µm

- MA300LD is designed for removal of foreign matter as well as oil mist (Element: 0.3µm)
- MA300LM is designed for removal of foreign matter as well as oil mist (Element: 0.01µm)

Specification

Model	MAF300LD/M	
Bore No.	8A	10A
Port size	1 / 4	3 / 8
Medium	Air	
Operating pressure range (*)	0.05~1 MPa	
Proof pressure	1.5 MPa	
Ambient temperature	- 5~+60°C (No freezing)	
Filter element	0.3 µm, 0.01 µm	
Drain capacity	35 cm ³	
Weight	300 g	

Order example

MAF300LD – 8A – ND – □

MODEL

FILTER ELEMENT
D: 0.3 µm
M: 0.01 µm

PORT SIZE
8A: 1/4
10A: 3/8

PORT THREAD
Blank: Rc thread
G: G thread
NPT: NPT thread

BOWL

Blank: PC bowl
N: Nylon bowl

OPTION

Blank: Standard type (Semi-auto drain)
D: Auto drain valve (FMRF300)

* Standard unit contains semi-auto-drain function when operating pressure below 0.05 MPa.

* Choose auto-drain FMRF300, the pressure range is 0.15~1 MPa.

